

Selection Guide For Type Number

TH ^① 1 0 — ^② N — ^③ 1 5 0 — ^④ N — ^⑤ 0 5 — ^⑥ K — ^⑦ A — ^⑧ N

1. Model Number :

10 11 12 . . .

2. Tube Dia :

N	None	A	1.6 ϕ	B	3.2 ϕ	C	5 ϕ	D	6.35 ϕ
E	8 ϕ	F	9.5 ϕ	G	12.7 ϕ	H	15 ϕ	I	22 ϕ
J	12.5 ϕ	K	4 ϕ	L	2.3 ϕ	As your order			

3. Tube Length :

000=0mm 050=50mm 100=100mm 150=150mm . . . As your order

4. Fitting Screw :

N	None	A	1/4 " -20UNC	B	5/16 " -24UNF	C	PT1/8 "
D	PT1/4 "	E	PT3/8 "	F	PT1/2 "	G	PT3/4 "
H	PF1/8 "	I	PF1/4 "	J	PF3/8 "	K	PF1/2 "
L	PF3/4 "	M	M6	P	M8	Q	1/4 " -Stainless
R	3/8 "						

5. Lead Wire Length :

00=None 01=0.1M 05=0.5M 10=1M 15=1.5M 20=2M 1T=10M
 A1=11M A2=12M A3=13M 2T=20M B1=21M . . . As your order

6. Element(type) :

N	None	K	K(CA)	J	J(IC)	P	PT(100 Ω)
R	R(PT-13%)	S	S(PT-10%)	T	T		

7. Wire Material :

		Wire material									
		Stainless Net Coat			Fiberglass Coat			PVC Coat (PVC)		Tafolon Coat	
NONE	N	CORE	0.65/1	A	0.65/1	D	0.65/1	I	0.65/1	k	
			0.32/4	B	0.32/4	E					
			0.65/1(I)	C	0.65/1(I)	F					
					0.32/4	G					
				0.32/7	H	0.32/4	J	0.32/4	L		

8. Isolated :

N Non-Isolated
 Y Isolated

Thermocouples

