

Block Mounts

SBM-MS



SBM-MT



SBM-PS



Features

- Three styles
- Sizes for most tubular sensor diameters
- Anodized aluminum or glass-filled nylon

Benefits

- Off-the-shelf mounting solution
- Secure attachment methods
- Easy installation

BLOCK MOUNTS

MODEL	SBM-MS-08	SBM-MS-12	SBM-MS-18	SBM-MS-30
A	8.05 (0.32)	12.1 (0.48)	18.4 (0.71)	30.1 (1.19)
B	15.8 (0.62)	22.2 (0.87)	31.7 (1.25)	50.8 (2.00)
C	25.4 (1.00)	38.1 (1.50)	44.5 (1.75)	63.5 (2.50)
D	19.0 (0.75)	19.0 (0.75)	25.4 (1.00)	34.9 (1.38)
E	18.4 (0.72)	24.8 (0.98)	34.3 (1.35)	51.5 (2.03)
F	3.58 (0.14)	5.08 (0.20)	6.61 (0.25)	6.73 (0.26)

MODEL	SBM-MT-08	SBM-MT-12	SBM-MT-18	SBM-MT-30
A	M8x1	M12x1	M18x1	M30x1.5
B	15.8 (0.62)	22.2 (0.87)	31.7 (1.25)	50.8 (2.00)
C	25.4 (1.00)	38.1 (1.50)	44.5 (1.75)	63.5 (2.50)
D	19.0 (0.75)	19.0 (0.75)	25.4 (1.00)	34.9 (1.38)
E	18.4 (0.72)	24.8 (0.98)	34.3 (1.35)	51.5 (2.03)
F	3.58 (0.14)	5.08 (0.20)	6.61 (0.25)	6.73 (0.26)

MODEL	SBM-PS-08	SBM-PS-12	SBM-PS-16	SBM-PS-18	SBM-PS-20	SBM-PS-22	SBM-PS-30	SBM-PS-36
A	8.05 (0.32)	12.1 (0.48)	16.1 (0.63)	18.1 (0.71)	20.1 (0.79)	22.1 (0.87)	30.1 (1.18)	36.1 (1.42)
B	27.0 (1.06)	32.0 (1.26)	36.0 (1.42)	45.0 (1.77)	55.0 (2.17)	61.0 (2.40)		
C	16.0 (0.63)	20.0 (0.97)	26.0 (1.02)	30.0 (1.18)	38.0 (1.50)	44.0 (1.73)		
D	12.0 (0.47)	12.0 (0.47)	12.0 (0.47)	15.0 (0.59)	18.0 (0.71)	18.0 (0.71)		
E	17.0 (0.67)	22.0 (0.87)	26.0 (1.02)	32.0 (1.26)	42.0 (1.65)	48.0 (1.89)		
F	4.50 (0.18)	4.50 (0.18)	4.50 (0.18)	5.50 (0.22)	5.50 (0.22)	5.50 (0.22)		

