

Angle Brackets



Features

- Multi-slotted for positioning versatility
- Each model is sized proportionally to sensor
- Zinc-plated CRS or 303 stainless steel

Benefits

- Eliminate hassles-source from our stock
- Rapid installation, setup and future adjustments
- Industry standard mounting footprint

MODEL	SAB-12	SAB-18	SAB-22	SAB-30	SAB-47
A	28.6 (1.13)	38.1 (1.50)	38.1 (1.50)	54.0 (2.13)	69.9 (2.75)
B	25.4 (1.00)		38.1 (1.50)		
C	3.18 (1.25)	34.9 (1.38)		50.8 (2.00)	63.5 (2.50)
D	12.1 (0.48)	18.1 (0.71)	22.1 (0.87)	30.1 (1.19)	47.2 (1.85)
E	13.5 (0.53)	19.8 (0.78)		30.1 (1.19)	47.2 (1.85)
F	19.8 (0.78)		28.7 (1.13)		
G	19.1 (0.75)	22.2 (0.88)	31.8 (1.25)	38.1 (1.50)	
H	3.18 (0.13)				

MODEL	SRAB-08	SRAB-12	SRAB-18	SRAB-22	SRAB-30	SRAB-47
A	25.4 (1.00)	28.7 (1.13)	50.8 (2.00)		63.5 (2.50)	88.9 (3.50)
B	28.7 (1.13)	34.8 (1.37)			44.5 (1.75)	50.8 (2.00)
C	31.8 (1.25)	38.1 (1.50)	44.5 (1.75)		57.2 (2.25)	63.5 (2.50)
D	8.74 (0.34)	12.7 (0.50)	19.1 (.750)	22.2 (.876)	30.5 (1.18)	25.4 (1.87)
E	7.92 (0.31)	13.9 (0.55)		17.4 (.685)	23.0 (0.91)	38.1 (1.50)
F	5.54 (0.22)				(7.14) (0.28)	
G	15.9 (.625)	19.1 (.750)	25.4 (1.00)	34.8 (1.37)	38.1 (1.50)	
H	11.9 (.468)	14.3 (.563)	14.3 (.563)	20.6 (.812)	25.4 (1.00)	
I	7.1 (.281)	7.92 (.312)	7.92 (.312)		10.3 (.406)	12.7 (.500)
J	1.78 (0.07)				2.16 (0.09)	3.05 (.120)
K	9.53 (0.38)	12.7 (0.50)	15.9 (0.63)	19.1 (0.75)		

