



Applications :

- SAP flow control
- granulate, powder control
- cellulose web weight control
- adhesive tape control
- frontal tape detection
- water glue coating control
- hot melt coating control
- splice and overlap detection
- packaged object detection

Advantages :

- versions for products, objects and endless materials
- adjustment for products and objects only needed once if at all
- very fast, 1000 meas./sec standard
- not sensitive to colour, contrast, light, transparency, pollution
- 24VDC power supply
- 24V switching or 0...10V output



QMS Sensor Versions



single sided sensor
 foil detection
 fleece detection
 glue control
 defect detection
 overlap detection
 shape control

Dimension : 60 x 20 x 100 mm

sensor version	order no.
QMS 70 for interval measurement with switching output, pnp	QMS70-INT-PNP
QMS 70 for interval measurement with analog output 0...10V	QMS70-INT-ANA
QMS 70 for permanent measurement with analog output 0...10V	QMS70-PERM-ANA
sensor including 5m connection cable	CE



single sided sensor
 foil detection
 object detection
 glue control
 defect detection

Dimension : 200 x 20 x 100 mm

sensor version	order no.
QMS 70-180 for interval measurement with switching output, pnp	QMS70-180-INT-PNP
QMS 70-180 for interval measurement with analog output 0...10V	QMS70-180-INT-ANA
QMS 70-180 for permanent measurement with analog output 0...10V	QMS70-180-PERM-ANA
sensor including 5m connection cable	CE



U-shaped sensor
 adhesive tape detection
 foil detection
 material control
 fleece detection
 defect detection

Dimension : 173 x 50 x 80 mm
 gap height : 10mm / 8mm

sensor version	order no.
QMS 70U-170 for interval measurement with switching output, pnp	QMS70U-170-INT-PNP
QMS 70U-170 for interval measurement with analog output 0...10V	QMS70U-170-INT-ANA
QMS 70U-170 for permanent measurement with analog output 0...10V	QMS70U-170-PERM-ANA
sensor including 5m connection cable	CE



single sided, round sensor
 non-woven web control
 textile web control

Dimension : \varnothing 120 x 60 mm

sensor version	order no.
QMS 70-120R for interval measurement with analog output 0...10V	QMS70-120R-INT-ANA
QMS 70-120R for permanent measurement with analog output 0...10V	QMS70-120R-PERM-ANA
sensor including 5m connection cable	CE



single sided sensor
 granulate flow control
 SAP flow control
 powder flow control

Dimension : 160 x 90 x 100 mm

sensor version	order no.
QMS 70-SAP for permanent measurement with analog output 0...10V	QMS70-SAP-PERM-ANA
sensor including 5m connection cable	CE



O-shaped sensor
 total product control
 diaper control
 feminine napkin control
 sensor of the HMC Profiler system

Dimension : 540 x 80 x 80 mm
 gap height : 20mm

sensor version	order no.
QMS 70-O-540 for interval measurement with analog output 0...10V	QMS70-O-540-INT-ANA
sensor including 5m connection cable	CE



O-shaped sensor
 non-woven web control
 cellulose web control
 textile web control

Dimension : 725 x 60 x 80 mm
 gap height : 8 mm

sensor version	order no.
QMS 70-O-745 for permanent measurement with analog output 0...10V	QMS70-O-725-PERM-ANA
sensor including 5m connection cable	CE

HOSSBACH Sensor Technologie